Technical specifications. The new BMW 4 Series Coupé. 420i.



		BMW 420i Coupé
Body		014
No of doors/seats		2/4
Length/width/height 1) (unladen)	mm	4768 / 1852 / 1383
Wheelbase	mm	2851
Track, front/rear	mm	1575 / 1611
Ground clearance	mm	127
Turning circle	m	11.4
Fuel tank capacity	approx. I	59
		5.25
Weight, unladen, to DIN/EU	kg	1525 / 1600
Max load to DIN	kg	490
Max permissible weight	kg	2015
Max axle load, front/rear	kg	970/1120
Max trailer load	kg	
braked (12%)/unbraked		1600 / 750
Max roofload/max towbar	kg	75/75
download		
Luggage comp capacity		440
Air resistance	c _d x A	0.25 x 2.19
Power Unit		
Config/No of cyls/valves		In-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High
3 3,		Precision Injection, VALVETRONIC fully variable valve timing,
		Double-VANOS variable camshaft timing
Effective capacity	CC	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		min. RON 91
Max output	kW/hp	135 / 184
at	rpm	5000 - 6500
Max torque	Nm	300
at	rpm	1350 - 4000
Electrical System	<u> </u>	00 /luggage comportment
Battery/installation	Ah/-	80 / luggage compartment
Driving Dynamics and Safety		
Suspension, front		Double-joint spring strut axle in lightweight aluminium-steel construction,
		hydraulically damped torque strut bearing
Suspension, rear		Five-link axle in lightweight aluminium-steel construction
Brakes, front		Vented disc brakes, with single-piston floating callipers
Brakes, rear		Vented disc brakes, with single-piston floating callipers
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC
		(Cornering Brake Control), DBC (Dynamic Brake Control), Performance
		Control, Dry Braking function, Fading Compensation, Start-Off Assistant;
		optional: Adaptive M suspension
Safety equipment	(Standard: airbags for driver and front passenger, side airbags for driver and
	fro	ont passenger, head airbags front and rear, three-point inertia-reel seatbelts
		on all seats with belt tensioner and belt force limiter at the front, crash
		sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS)
		with Servotronic function, optional: variable sport steering
Steering ratio, overall	:1	14.1
Tyres, front/rear		225/50 R17 98Y XL

		BMW 420i Coupé
Transmission		
Type of transmission		Eight-speed Steptronic transmission
Gear ratios I	:1	5.250
II	:1	3.360
	:1	2.172
IV	:1	1.720
V	:1	1.136
VI	:1	1.000
VII	:1	0.823
VIII	:1	0.640
R	:1	3.712
Final drive	:1	2.813
Performance		
Power-to-weight ratio (DIN)	kg/kW	10.9 (11.1)
Output per litre	kW/I	67.6
Acceleration 0–100 km/h	S	7.5
Top speed	km/h	240

BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, Electric Power Steering, Auto Start Stop function, Optimum Shift Indicator, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance

Fuel Consumption EC	E		
Urban	l/100 km	7.2 - 6.6	
Extra-urban	l/100 km	5.0 - 4.6	
Combined	l/100 km	5.8 – 5.3	
CO ₂	g/km	132 – 122	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

1) Height including roof fin

²⁾ Oil change

The fuel consumption, CO₂ emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions, the CO₂ values may differ from the values stated here (depending on national legislation).

The new BMW 4 Series Coupé. 430i.

		BMW 430i Coupé	
Body No of doors/seats		2/4	
Length/width/height ¹⁾ (unladen)	mm	4768 / 1852 / 1383	
Wheelbase	mm	2851	
Track, front/rear		1575/1611	
Ground clearance	mm	127	
	mm		
Turning circle	m	<u> </u>	
Fuel tank capacity Engine oil ²⁾	approx. I	5.25	
Weight, unladen, to DIN/EU		1545 / 1620	
Max load to DIN	kgkg	485	
Max permissible weight	kgkg	2030	
	kg		
Max axle load, front/rear	kg	980 / 1120	
Max trailer load	kg	1000/750	
braked (12%)/unbraked			
Max roofload/max towbar download	kg	15175	
Luggage comp capacity		440	
Air resistance	c _d x A	0.25 x 2.19	
Power Unit			
Config/No of cyls/valves		In-line / 4 / 4	
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing	
Effective capacity	CC	1998	
Stroke/bore	mm	94.6 / 82.0	
Compression ratio	:1	10.2	
Fuel		min. RON 91	
Max output	kW/hp	190/258	
at	rpm	5000 - 6500	
Max torque	Nm	400	
at	rpm	1550 – 4400	
Electrical System			
Battery/installation	Ah/–	80 / luggage compartment	
Driving Dynamics and Safety			
Suspension, front		Double-joint spring strut axle in lightweight aluminium-steel construction,	
		hydraulically damped torque strut bearing	
Suspension, rear		Five-link axle in lightweight aluminium-steel construction	
Brakes, front		Vented disc brakes, with single-piston floating callipers	
Brakes, rear		Vented disc brakes, with single-piston floating callipers	
Driving stability systems	Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Performance Control, Dry Braking function, Fading Compensation, Start-Off Assistant; optional: Adaptive M suspension, M Sport differential		
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and ont passenger, head airbags front and rear, three-point inertia-reel seatbelts on all seats with belt tensioner and belt force limiter at the front, crash sensors, tyre pressure indicator	
Steering		Electric Power Steering (EPS)	
Steering		Electric Power Steering (EPS) with Servotronic function, optional: variable sport steering	
Steering Steering ratio, overall	:1	= 1 1	
Steering Steering ratio, overall Tyres, front/rear	:1	with Servotronic function, optional: variable sport steering	

	BMW 430i Coupé
	Eight-speed Steptronic transmission
:1	5.250
:1	3.360
:1	2.172
:1	1.720
:1	1.136
:1	1.000
:1	0.823
:1	0.640
:1	3.712
:1	2.813
kg/kW	8.1
kW/I	95.1
S	5.8
km/h	250
	:1 :1 :1 :1 :1 :1 :1 :1 :1 :1 :1 :1 :1 :

BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, Electric Power Steering, Auto Start Stop function, Optimum Shift Indicator, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance

Fuel Consumption EC)E		
Urban	l/100 km	7.7 – 7.3	
Extra-urban	l/100 km	5.3 - 4.8	
Combined	l/100 km	6.1 – 5.7	
CO ₂	g/km	141 – 131	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

1) Height including roof fin

²⁾ Oil change

The fuel consumption, CO₂ emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions, the CO₂ values may differ from the values stated here (depending on national legislation).

The new BMW 4 Series Coupé. M440i xDrive.

	BMW M440i xDrive Coupé		
Body			
No of doors/seats		2/4	
Length/width/height 1) (unladen)	mm	4770 / 1852 / 1393	
Wheelbase	mm	2851	
Track, front/rear	mm	1575/1611	
Ground clearance	mm	129	
Turning circle		12.0	
Fuel tank capacity	m	59	
Engine oil 2)	approx. I	6.5	
Neight, unladen, to DIN/EU		1740 / 1815	
	kg	505	
Max load to DIN	kg		
Max permissible weight	kg	2245	
Max axle load, front/rear	kg	1110/1190	
Max trailer load	kg		
praked (12%)/unbraked		1800 / 750	
Max roofload/max towbar download	kg	75/75	
Luggage comp capacity	1	440	
Air resistance	Cd X A	0.29 x 2.19	
Power Unit			
Config/No of cyls/valves		In-line / 6 / 4	
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High	
0 07		Precision Injection, VALVETRONIC fully variable valve timing,	
		Double-VANOS variable camshaft timing	
Effective capacity	CC	2998	
Stroke/bore	mm	94.6 / 82.0	
Compression ratio	:1	10.2	
Fuel		min. RON 91	
Max output	kW/hp	275/374	
at	rpm	5500 - 6500	
Max torque	Nm	500	
		1900 – 5000	
at 48V mild hybrid technology	rpm	1900 - 5000	
	W//ba	0./11	
Max output	kW/hp	8/11	
Electrical System			
12V battery/installation	Ah/-	80 / luggage compartment	
48V battery/installation	Ah/-	11 / engine compartment	
	7-411/		
Driving Dynamics and Safety			
Suspension, front		Double-joint spring strut axle in lightweight aluminium-steel construction,	
		hydraulically damped torque strut bearing	
Suspension, rear		Five-link axle in lightweight aluminium-steel construction	
Brakes, front		Vented disc brakes, with four-piston fixed callipers	
Brakes, rear		Vented disc brakes, with single-piston floating callipers	
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Performance	
	0		
		Control, Dry Braking function, Fading Compensation, Start-Off Assistant, al wheel-drive system xDrive linked with DSC, M Sport differential; optional:	
		Adaptive M suspension	
Safaty aquipmont			
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelt		
	110		
		on all seats with belt tensioner and belt force limiter at the front, crash	
Stooring		sensors, tyre pressure indicator	
Steering		Electric Power Steering (EPS)	
0		variable sport steering with Servotronic function	
Steering ratio, overall	:1	13.6	
Tyres, front/rear		225/45 R18 95Y XL	
		255/40 R18 99Y XL	
Rims, front/rear		7.5J x 18 light-alloy/	
		8.5J x 18 light-alloy	

			BMW M440i xDrive Coupé	
Transmission	1			
Type of transm	ission		Eight-speed Steptronic transmission	
Gear ratios		:1	5.250	
		:1	3.360	
		:1	2.172	
	IV	:1	1.720	
	V	:1	1.136	
	VI	:1	1.000	
	VII	:1	0.823	
	VIII	:1	0.640	
	R	:1	3.712	
Final drive		:1	2.813	
Performance				
Power-to-weig	ht ratio (DIN)	kg/kW	6.3	
Output per litre	1	kW/I	91.7	
Acceleration	0–100 km/h	S	4.5	
Top speed		km/h	250	
BMW Efficien	tDynamics			
BMW EfficientDynamics standard		Mild hybrid technology with 48V starter-generator, Brake Energy		
features			Regeneration with recuperation display, Auto Start Stop function, ECO PR and COMFORT mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweigh	

wheel drive, differential with optimised warm-up behaviour, tyres with reduced rolling resistance

optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-

Fuel Consumption E	CE		
Urban	l/100 km	9.0 - 8.6	
Extra-urban	l/100 km	6.0 - 5.7	
Combined	l/100 km	7.1 – 6.8	
CO ₂	g/km	161 – 155	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Height including roof fin ²⁾ Oil change

The fuel consumption, CO₂ emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions, the CO₂ values may differ from the values stated here (depending on national legislation).

The new BMW 4 Series Coupé. 420d.

	BMW 420d Coupé			
Body				
No of doors/seats		2/4		
Length/width/height ¹⁾ (unladen)	mm	4768 / 1852 / 1383		
Wheelbase	mm	2851		
Track, front/rear	mm	1575 / 1611		
Ground clearance	mm	127		
Turning circle	m	11.4		
Fuel tank capacity	approx. I	59		
Engine oil 2)	I	5.5		
Weight, unladen, to DIN/EU	kg	1605 / 1680		
Max load to DIN	kg	490		
Max permissible weight	kg	2095		
Max axle load, front/rear	kg	1020 / 1160		
Max trailer load	kg			
braked (12%)/unbraked	0	1600 / 750		
Max roofload/max towbar	kg	75/75		
download	Ū			
Luggage comp capacity		440		
Air resistance	c _d x A	0.25 x 2.19		
Power Unit				
Config/No of cyls/valves		In-line / 4 / 4		
Engine technology		BMW TwinPower Turbo technology: multi-stage turbocharging,		
		common-rail direct injection with solenoid injectors		
		(max. injection pressure: 2500 bar)		
Effective capacity	CC	1995		
Stroke/bore	mm	90.0/84.0		
Compression ratio	:1	16.5		
Fuel		Diesel		
Max output	kW/hp	140 / 190		
at	rpm	4000		
Max torque	Nm	400		
at	rpm	1750 – 2500		
48V mild hybrid technology				
Max output	kW/hp	8/11		
Electrical System				
12V battery/installation	Ah/–	70 / luggage compartment		
48V battery/installation		11 / engine compartment		
	An/-	r r engine compartment		
Driving Dynamics and Safety				
Suspension, front		Double-joint spring strut axle in lightweight aluminium-steel construction,		
		hydraulically damped torque strut bearing		
Suspension, rear		Five-link axle in lightweight aluminium-steel construction		
Brakes, front		Vented disc brakes, with single-piston floating callipers		
Brakes, rear		Vented disc brakes, with single-piston floating callipers		
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC		
		(Cornering Brake Control), DBC (Dynamic Brake Control), Performance		
	Control, Dry Braking function, Fading Compensation, Start-Off Assistant;			
		optional: Adaptive M suspension		
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and		
	front passenger, head airbags front and rear, three-point inertia-reel seatbelts			
		on all seats with belt tensioner and belt force limiter at the front, crash		
		sensors, tyre pressure indicator		
Steering		Electric Power Steering (EPS)		
0		with Servotronic function, optional: variable sport steering		
Steering ratio, overall	:1	14.1		
Steering ratio, overall Tyres, front/rear	:1	14.1 225/50 R17 98Y XL		

			BMW 420d Coupé
Transmissio	1		
Type of transm	nission		Eight-speed Steptronic transmission
Gear ratios		:1	5.250
	I	:1	3.360
		:1	2.172
	IV	:1	1.720
	V	:1	1.136
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	2.813
Performance			
Power-to-weig	ht ratio (DIN)	kg/kW	11.5
Output per litre	9	kW/I	70.2
Acceleration	0–100 km/h	S	7.1
Top speed		km/h	240
BMW Efficier	ntDynamics		
BMW Efficient	Dynamics standard		Mild hybrid technology with 48V starter-generator, Brake Energy
features		Regeneration with recuperation display, Auto Start Stop function, ECO PRC and COMFORT mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance.	

BMW Blue Performance technology with SCR catalytic converter

Fuel Consumption E	CE		
Urban	l/100 km	4.9 - 4.5	
Extra-urban	l/100 km	3.9 – 3.6	
Combined	l/100 km	4.2 - 3.9	
CO ₂	g/km	112 – 103	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Height including roof fin ²⁾ Oil change

The fuel consumption, CO₂ emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions, the CO₂ values may differ from the values stated here (depending on national legislation).

The new BMW 4 Series Coupé. 420d xDrive.

	BMW 420d xDrive Coupé			
Body				
No of doors/seats		2/4		
Length/width/height 1) (unladen)	mm	4768 / 1852 / 1390		
Wheelbase	mm	2851		
Track, front/rear	mm	1575 / 1611		
Ground clearance	mm	126		
Turning circle		12.0		
Fuel tank capacity	m	59		
Engine oil ²⁾	approx. I	5.5		
Weight, unladen, to DIN/EU		1670 / 1745		
Max load to DIN	kg			
	kg	495		
Max permissible weight	kg	2165		
Vlax axle load, front/rear	kg	1070 / 1170		
Max trailer load	kg	1000/750		
oraked (12%)/unbraked		1800 / 750		
Vlax roofload/max towbar	kg	75/75		
download				
Luggage comp capacity		440		
Air resistance	c _d x A	0.25 x 2.19		
Power Unit				
Config/No of cyls/valves		In-line / 4 / 4		
Engine technology		BMW TwinPower Turbo technology: multi-stage turbocharging,		
		common-rail direct injection with solenoid injectors		
		(max. injection pressure: 2500 bar)		
Effective capacity	CC	1995		
Stroke/bore	mm	90.0 / 84.0		
Compression ratio	:1	16.5		
Fuel		Diesel		
Max output	kW/hp	140 / 190		
at	rpm	4000		
Max torque	Nm	400		
at	rpm	1750 – 2500		
48V mild hybrid technology				
Max output	kW/hp	8/11		
Flaatsiaal Constant				
Electrical System	AL /	70.11		
12V battery/installation	Ah/-	70 / luggage compartment		
48V battery/installation	Ah/-	11 / engine compartment		
Driving Dynamics and Safety				
Suspension, front	Double-joint spring strut axle in lightweight aluminium-steel construction,			
		hydraulically damped torque strut bearing		
Suspension, rear		Five-link axle in lightweight aluminium-steel construction		
Brakes, front	Vented disc brakes, with single-piston floating callipers			
Brakes, rear	Vented disc brakes, with single-piston floating callipers			
Driving stability systems	Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC			
	(Cornering Brake Control), DBC (Dynamic Brake Control), Performance			
	(Control, Dry Braking function, Fading Compensation, Start-Off Assistant,		
		xDrive all-wheel-drive system linked with DSC;		
		optional: Adaptive M suspension		
Safety equipment	S	Standard: airbags for driver and front passenger, side airbags for driver and		
	fro	ont passenger, head airbags front and rear, three-point inertia-reel seatbel		
	on all seats with belt tensioner and belt force limiter at the front, crash			
	sensors, tyre pressure indicator			
Steering	Electric Power Steering (EPS)			
		with Servotronic function, optional: variable sport steering		
Steering ratio, overall	:1	14.9		
Steering ratio, overall Tyres, front/rear	:1	14.9 225/50 R17 98Y XL		

			BMW 420d xDrive Coupé
Transmission			
Type of transmiss	sion		Eight-speed Steptronic transmission
Gear ratios		:1	5.250
		:1	3.360
		:1	2.172
	IV	:1	1.720
	V	:1	1.136
	VI	:1	1.000
	VI	:1	0.823
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	2.813
Performance			
Power-to-weight ratio (DIN)		kg/kW	11.9
Output per litre		kW/I	70.2
Acceleration	0–100 km/h	S	7.4
Top speed		km/h	238

BMW EfficientDynamics

BMW EfficientDynamics standard features

Mild hybrid technology with 48V starter-generator, Brake Energy Regeneration with recuperation display, Auto Start Stop function, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised allwheel drive, differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology with SCR catalytic converter

Fuel Consumption ECE					
Urban	l/100 km	5.2 - 4.8			
Extra-urban	l/100 km	4.2 - 4.0			
Combined	l/100 km	4.6 - 4.3			
CO ₂	g/km	121 – 112			
Emission rating		Euro 6d			

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

1) Height including roof fin

²⁾ Oil change

The fuel consumption, CO₂ emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions, the CO₂ values may differ from the values stated here (depending on national legislation).

BMW Media Information

06/2020 Page 11 **Exterioar and interior dimensions.** The new BMW 4 Series Coupé.







